



Certificate No.: 1108-5913

Certificate holder: Aquaform AG, Gewerbestrasse 16, CH-4105 Biel-Benken

In accordance with our regulation ZW101 „general terms and conditions of the SGWA certification body water“ the SGWA certify the following serial products:

Rubric: Pipe coupling
Denomination: HymaxGrip
Types: Restraint coupling, with one screw per side, DN 40 - DN 200
Restraint coupling, with two screws per side, DN 175 - DN 300
Reducer, with one screw per side, DN 65 - 200 / DN 40 - 150
Reducer, with two screw per side, DN 200 - 300 / DN 150 - 250
Flange Adapter, with one screw, DN 80 - 200
Flange Adapter with two screws, DN 175 - 300
End Caps, with one screw, DN 40 - 200
End Caps, with two screws, DN 100 - 300

DN: 40...300 PN: 16 tmax: 25 °C

Certification Standard: SGWA ZW163 (07/22), EN 14525 (2004)

Validity: 31.05.2027

Conditions (C) / Remarks (R):

(R) Restricted scope of testing compared to EN 14525 (2004), table 4, remark a):

This means, that no tests were carried out with pipes made of PVC. In the tests of the PE pipes, those made of the material PE 100 with SDR 17 (PN 10) or SDR 11 (PN 16) were used.

The applicant is entitled to offer the above mentioned products as certificated by the SGWA and to use the above SGWA-conformity mark (publication in the list of certificates water).

Swiss Gas and Water Industry Association
Certification body water

Javier Fernandez
Head

Rubric: Pipe coupling

Denomination: HymaxGrip

Types	DN	PN	C°	Acoustic group	Losses kWh/24 h / ErP Class	Content	Index	Metrology
HymaxGrip Restraint Coupling, with one screw per side								
Ø 39 - 56 / Ø 55 - 67	40 ... 50	16	25	-	-	-	9	-
Ø 59 - 76 / Ø 75 - 87	65	16	25	-	-	-	9	-
Ø 80 - 95 / Ø 94 - 106	80	16	25	-	-	-	9	-
Ø 106 - 118 / Ø 117 - 130	100	16	25	-	-	-	9	-
Ø 130 - 146 / Ø 145 - 162	125	16	25	-	-	-	9	-
Ø 158 - 174 / Ø 173 - 190	150	16	25	-	-	-	9	-
Ø 198 - 214 / Ø 213 - 230	200	16	25	-	-	-	9	-
HymaxGrip Restraint Coupling, with two screws per side								
Ø 190 - 215 / Ø 214 - 240	175 ... 200	16	25	-	-	-	9	-
Ø 214 - 239 / Ø 238 - 264	200 ... 225	16	25	-	-	-	9	-
Ø 266 - 291 / Ø 290 - 316	250	16	25	-	-	-	9	-
Ø 312 - 337 / Ø 336 - 362	300	16	25	-	-	-	9	-
HymaxGrip Reducer Coupling, with one screw per side								
Ø 59 - 87 / Ø 39 - 67	65 / 40 .. 50	16	25	-	-	-	9	-
Ø 80 - 106 / Ø 59 - 87	80 / 65	16	25	-	-	-	9	-
Ø 106 - 130 / Ø 80 - 106	100 / 80	16	25	-	-	-	9	-
Ø 130 - 162 / Ø 106 - 130	125 / 100	16	25	-	-	-	9	-
Ø 158 - 174 / Ø 173 - 190	150 / 125	16	25	-	-	-	9	-
Ø 158 - 190 / Ø 106 - 130	150 / 100	16	25	-	-	-	9	-
Ø 198 - 230 / Ø 130 - 162	200 / 125	16	25	-	-	-	9	-
Ø 198 - 230 / Ø 158 - 190	200 / 150	16	25	-	-	-	9	-
HymaxGrip Reducer Coupling, with two screws per side								
Ø 214 - 264 / Ø 158 - 190	200 / 150	16	25	-	-	-	9	-
Ø 214 - 264 / Ø 190 - 240	200 / 175	16	25	-	-	-	9	-
Ø 266 - 316 / Ø 214 - 264	250 / 200	16	25	-	-	-	9	-
Ø 312 - 362 / Ø 266 - 316	300 / 250	16	25	-	-	-	9	-
HymaxGrip Flange Adapter, with one screw								
Ø 80 - 95 / Ø 94 - 106	80	16	25	-	-	-	9	-
Ø 106 - 118 / Ø 117 - 130	100	16	25	-	-	-	9	-
Ø 130 - 146 / Ø 145 - 162	125	16	25	-	-	-	9	-
Ø 158 - 174 / Ø 173 - 190	150	16	25	-	-	-	9	-
Ø 198 - 214 / Ø 213 - 230	200	16	25	-	-	-	9	-
HymaxGrip Flange Adapter, with two screws								
Ø 190 - 215 / Ø 214 - 240	175	16	25	-	-	-	9	-
Ø 214 - 239 / Ø 238 - 264	200	16	25	-	-	-	9	-
Ø 266 - 291 / Ø 290 - 316	250	16	25	-	-	-	9	-
Ø 312 - 337 / Ø 336 - 362	300	16	25	-	-	-	9	-
HymaxGrip End Cap, with one screw								
Ø 39 - 56 / Ø 55 - 67	40 ... 50	16	25	-	-	-	9	-
Ø 59 - 76 / Ø 75 - 87	65	16	25	-	-	-	9	-
Ø 80 - 95 / Ø 94 - 106	80	16	25	-	-	-	9	-
Ø 106 - 118 / Ø 117 - 130	100	16	25	-	-	-	9	-
Ø 130 - 146 / Ø 145 - 162	125	16	25	-	-	-	9	-
Ø 158 - 174 / Ø 173 - 190	150	16	25	-	-	-	9	-
Ø 198 - 214 / Ø 213 - 230	200	16	25	-	-	-	9	-
HymaxGrip End Cap, with two screws								
Ø 190 - 215 / Ø 214 - 240	175	16	25	-	-	-	9	-
Ø 214 - 239 / Ø 238 - 264	200	16	25	-	-	-	9	-
Ø 266 - 291 / Ø 290 - 316	250	16	25	-	-	-	9	-
Ø 312 - 337 / Ø 336 - 362	300	16	25	-	-	-	9	-
HymaxGrip Adaptor, with one screw								
Ø 104 - 118 / Ø 117 - 130	100	16	25	-	-	-	9	-
Ø 130 - 146 / Ø 145 - 162	125	16	25	-	-	-	9	-
Ø 158 - 174 / Ø 173 - 190	150	16	25	-	-	-	9	-
Ø 198 - 214 / Ø 213 - 230	200	16	25	-	-	-	9	-